

## DÜŞÜK BASINÇ HAVALI Otomatik Püskürtme Tabancası

M25

dermix®

Low Pressure Airspray Automatic Spray Gun

### TEKNİK ÖZELLİKLER

Technical Properties

ÇALIŞMA BASINCI	Working Pressure	: 3 Bar
SIVI BASINCI	Fluid Pressure	: 0.2 - 2 Bar
HAVA BASINCI	Air Pressure	: 3 - 6 Bar
TETİK HAVA GİRİŞİ	Valve Air Input	: 1/8"
SIVI GİRİŞİ	Liquid Input	: 1/8"
ÖLÇÜLER (E x B x Y)	Dimensions (W x L x H)	: 35 x 50 x 66 mm
AĞIRLIK	Weight	: 173 gr
İĞNE SEÇENEKLERİ	Needle Options	: 0.8 - 1.0 - 1.2 mm

### KULLANIM ALANLARI


Applications

- KALIP YAĞLAMA ÜNİTELERİ Mold Lubrication Systems
- NEMLENDİRME SİSTEMLERİ Moistening Systems
- HATA KONTROL ÜNİTELERİ Error Check Systems
- BOYAMA HATLARI Paint Lines
- KAPLAMA SİSTEMLERİ Covering Systems
- YAPIŞTIRICI PÜSKÜRTME Adhesive Spraying
- SOĞUTMA SİSTEMLERİ Cooling Systems
- GENEL YAĞLAMA SİSTEMLERİ Genel Lubrication Systems

### DETAYLAR

Details

#### ERGONOMİK BOYUTLAR Ergonomic Dimensions



#### PÜSKÜRTME GENİŞLİK AYARI Spray Width Setting



#### HASSAS SIVI AYARI Precision Fluid Setting

